



Polaris Polyurethane/Polyurea

Simple and Maintenance-Free, The Polaris System is Available In 22:1 Pump Ratio For Spray or Pour Applications

These Systems Are Built Tough and Feature Dual 2.0 GPM Stainless Steel Fluid Pumps With Triple Upper Seals to Prevent Moisture Attack. In Addition, Quick-Pin Disassembly Provides For Rapid Pump Rebuild or Replacement.

This System Processes Coatings, Adhesives, Polyurethane Foams, Polyurethane Elastomers, Polyureas And More With Absolute Ease! This With The Addition Of Optional Line Heaters, a Hose Heater, and Our Programmable Dispense Meter, This System Can Become The Ultimate In 2-Component Dispense Technology.

Features:

- Material Pump Quick Pin Disassembly
- Triple "No Leak" Upper Seals
- Long Wearing Pump Piston Seals
- Variable Output
- Variable Spray Pattern
- Hardened Components
- Stainless Steel/Teflon Hoses
- Several Mounting Options Available
- Spare Parts Kits
- Std. 1 Year Warranty

Pressure: 2000 PSI Maximum pressure (138 BAR)

Power Requirement: 15 CFM @ 30 strokes per minute

Maximum Flow: 2 GPM @ 60 Cycles per Minute

There is no Filter

Temp Requirement: Minimum temp 50 degrees Fahrenheit to 200 degrees Fahrenheit maximum.

Pumps: (2) 1 GPM reciprocating pumps. Pumps are self priming

Hose: Maximum length of system hose to gun is 200 feet.

Our systems are shipped with standard 50 foot hoses.

"Polaris" Series Systems: High Quality, Durable And Worry-Free At A Superior Price...



POWERFUL, DEPENDABLE...SOLID PERFORMANCE

For More Information And A Local Distributor
Call Us At (727)393-1818 or Visit www.phoenixequipment.com

Phoenix Composites Equipment
11715 87th St
Largo, FL 33773
P: (727) 393-1818
F: (727) 393-1010
www.phoenixequipment.com

